eSMART10 Tech-Note

HMI 10” TFT Resistive touch, 4 GB Flash memory, 1x Ethernet

- 10.1” TFT color display, LED backlight
- 1024x600 pixel (WVGA) resolution, 64K colors
- Resistive touchscreen
- Ethernet port
- USB port

Highlights

The eSMART Series HMI products combine state-of-the-art features and top performance with an oustanding design. They have been designed to offer an outstanding price/performance ratio for challenging applications. They are the ideal choice for HMI applications including factory and building automation.
eSMART10 features a bright 10.1” TFT widescreen (16:9) display with a fully dimmable LED backlight

- Compatible with JMobile Studio.
- Full vector graphic support. Native support of SVG graphic objects, trasparency and alpha blending.
- Screen object dynamics: control visibility and transparency, move, resize, rotate any object on screen. Change properties of basic and complex objects.
- Multilanguage applications with TrueType fonts. Easily create, install and maintain applications in multiple languages to meet global requirements.
- Data display in numerical, text, bargraph, analog gauges and graphic image formats.
- Rich set of state-of-the-art HMI features: data acquisition and logging, trend presentation, alarm handling, scheduler and timed actions (daily and weekly schedulers, exception dates), recipes, security and user management, e-mail and RSS feeds.
- Wide selection of communication drivers available with multiple-driver communication capability.
- Remote monitoring and control with Client-Server functionality.
- Off-line and on-line simulation with JMobile Studio.
- Powerful scripting language for automating HMI applications. Efficient script debugger improves productivity in application development.
- Rich gallery of objects and symbols

© 2015 EXOR International S.p.A. - Subject to change without notice

eSMART10 - Technical Data

System Resources	
Display - Colors	10.1" TFT 16:9 - 64K
Resolution	1024x600, WVGA
Brightness	200 Cd/m² typ.
Dimming	Yes
Touchscreen	Resistive
CPU	32-bit RISC single core - 1 GHz
Operating System	Linux 3.12
Flash	4 GB
RAM	512 MB
Real Time Clock, RTC Back-up, Buzzer	Yes
Interface	
Ethernet port	1 (port 0 - 10/100)
USB port	1 (Host v. 2.0, max. 500 mA)
Serial port	1 (RS-232, RS-485, RS-422, software configurable)
SD card	No
Expansion	No
Ratings	
Power supply	24 Vdc (10 to 32 Vdc)
Current Consumption	0.38 A at 24 Vdc (max.)
Input Protection	Automatic
Battery	Yes (Supercapacitor)
Environment Conditions	
Operating Temp	0 to 50 °C (vertical installation)
Storage Temp	-20°C to +70°C
Operating / Storage Humidity	5-85% RH, non condensing
Protection Class	IP66 (front), IP20 (rear) Type: 2, 4X
Dimensions and Weights	
Faceplate LxH	282x197 mm (11.10x7.80")
Cutout AxB	271x186 mm (10.66x7.32")
Depth D+T	29+6 mm (1.14+0.23")
Weight	Approx 1.0 Kg
Approvals	
CE	Electromagnetic Compatibility (EMC) - Directive 2014/30/EU
ATEX	Zone 2: II 3 G Ex ic ec IIC T6 Gc
UL	cULus: UL508
UL	cULus: Class 1 Div 2
DNV-GL	Yes
EU RO MR	Yes
RCM	Yes





1 Serial Port
2 Ethernet Port
3 USB port (version 2.0 - 1.1)
4 Power Supply





Cut-out

Ordering Information

Model	Part Number	Description
eSMART10	+ESMA10U301	HMI 10" TFT, 1024x600, Resistive touch, 4 GB Flash memory, 1x Ethernet, JMobile runtime

© 2015 EXOR International S.p.A. - Subject to change without notice